



Cable Simulator, 550/625 MHz

For Broadband International[®] FAST-PAC[™] Amplifiers

BROADBAND INTERNATIONAL [®] FAST-PAC [™] 550 and 625 MHz SERIES CABLE SIMULATORS		
PARAMETER	SPECIFICATION	Unit
Passband	50-550/625	MHz
Flatness	+/-3	dB
Insertion Loss (Max)	1	dB
Values	1 to 10	dB

Part Number	EQ Value	Slope at 625 MHz	Slope at 550 MHz	Insertion Loss	105	300	450	550	625
21E601C	1	0.7	0.7	1	1.1	1.4	1.6	1.7	1.7
21E602C	2	1.5	1.4	1	1.2	1.8	2.1	2.4	2.5
21E603C	3	2.2	2.0	1	1.4	2.2	2.7	3.0	3.2
21E604C	4	3.0	2.7	1	1.5	2.6	3.3	3.7	4.0
21E605C	5	3.7	3.4	1	1.6	3.1	3.9	4.4	4.7
21E606C	6	4.5	4.0	1	1.7	3.5	4.4	5.0	5.5
21E607C	7	5.2	4.7	1	1.9	3.9	5.0	5.7	6.2
21E608C	8	5.9	5.4	1	2.0	4.3	5.6	6.4	6.9
21E609C	9	6.7	6.1	1	2.1	4.7	6.2	7.1	7.7
21E610C	10	7.4	6.7	1	2.2	5.1	6.7	7.7	8.4