



# Cable Simulator, 750/870 MHz

For Broadband International<sup>®</sup> FAST-PAC<sup>™</sup> Amplifiers

BROADBAND INTERNATIONAL FASTPAC 750 and 870 MHz SERIES CABLE SIMULATORS		
PARAMETER	SPECIFICATION	Unit
Passband	50-750/870	MHz
Flatness	+/- .3	dB
Insertion Loss (Max)	1	dB
Values	1 to 12	dB

Part Number	EQ Value	Slope	Insertion loss							
			50	105	300	450	550	650	750	870
21E701C	1	-0.80	0.8	0.90	1.10	1.30	1.35	1.40	1.50	1.60
21E702C	2	-1.60	0.8	1.00	1.50	1.70	1.90	2.10	2.20	2.40
21E703C	3	-2.40	0.8	1.10	1.80	2.20	2.50	2.70	2.90	3.20
21E704C	4	-3.10	0.8	1.20	2.20	2.70	3.00	3.30	3.60	3.90
21E705C	5	-3.90	0.8	1.30	2.50	3.20	3.60	4.70	4.30	4.70
21E706C	6	-4.70	0.8	1.40	2.80	3.70	4.20	4.60	5.00	5.50
21E707C	7	-5.50	0.8	1.50	3.20	4.10	4.70	5.20	5.70	6.30
21E708C	8	-6.30	0.8	1.60	3.50	4.60	5.30	5.90	6.40	7.10
21E709C	9	-7.10	0.8	1.70	3.90	5.10	5.80	6.50	7.10	7.90
21E710C	10	-7.90	0.8	1.80	4.20	5.60	6.40	7.10	7.80	8.70
21E711C	11	-8.60	0.8	1.90	4.50	6.00	6.90	7.80	8.50	9.40
21E712C	12	-9.40	0.8	2.00	4.87	6.50	7.50	8.41	9.30	10.20