



Forward Equalizer, 870 MHz, FAST-PAC™

For Broadband International® FAST-PAC™ Amplifiers

PARAMETER	SPECIFICATION	Unit
Passband	50-870	MHz
Flatness	+/- 0.3	dB
Insertion Loss (Max)	1.2	dB

BBI Part #	Value	Slope	50	200	300	450	550	650	750	870
21E000	0	0	0	0	0	0	0	0	0	0
21E801	1	0.8	1.8	1.5	1.4	1.3	1.2	1.2	1.1	1
21E802	2	1.6	2.6	2	1.8	1.6	1.4	1.3	1.1	1
21E803	3	2.3	3.3	2.6	2.2	1.8	1.6	1.4	1.2	1
21E804	4	3	4	3.1	2.7	2.1	1.8	1.5	1.3	1
21E805	5	3.7	4.7	3.7	3.2	2.4	2	1.7	1.4	1
21E806	6	4.6	5.6	4.1	3.5	2.7	2.2	1.8	1.4	1
21E807	7	5.3	6.3	4.6	3.9	3	2.4	1.9	1.5	1
21E808	8	6.2	7.2	5.2	4.3	3.2	2.6	2.1	1.6	1
21E809	9	6.8	7.8	5.7	4.7	3.5	2.8	2.2	1.6	1
21E810	10	7.6	8.6	6.2	5.1	3.8	3	2.4	1.7	1
21E811	11	8.4	9.4	6.7	5.5	4.1	3.3	2.5	1.8	1
21E812	12	9.1	10.1	7.2	6	4.5	3.5	2.6	1.9	1
21E813	13	9.9	10.9	7.8	6.4	4.7	3.7	2.8	1.9	1
21E814	14	10.6	11.6	8.3	6.8	4.9	3.9	2.9	2	1
21E815	15	11.4	12.4	8.9	7.2	5.2	4.1	3	2.1	1
21E816	16	12.2	13.2	9.3	7.6	5.5	4.3	3.2	2.1	1
21E817	17	13	14	9.8	8	5.8	4.5	3.3	2.2	1
21E818	18	13.8	14.8	10.4	8.4	6.1	4.7	3.4	2.3	1
21E819	19	14.4	15.4	10.9	8.8	6.3	4.9	3.6	2.4	1
21E820	20	15.2	16.2	11.4	9.3	6.6	5.1	3.7	2.4	1
21E821	21	16	17	12	9.7	7	5.3	3.8	2.5	1
21E822	22	16.9	17.9	12.6	10.1	7.2	5.5	4	2.7	1
21E823	23	17.6	18.6	13.2	11.3	8.1	6.3	4.5	2.9	1
21E824	24	18.9	19.9	14.4	11.8	8.4	6.5	4.6	3	1