

# Power Supply and Umbilical Cord/Ladder Tray for Gainmaker Style System Amplifier

For Broadband International® 1.2 GHz 4PAC-G and Cisco® GainMaker® System Amplifiers



The power supply and umbilical cord/ladder tray install into any existing 1 GHz or 1.2 GHz GainMaker®, or 1.2 GHz Broadband International® system amplifier housing with lid cover power supply option.

## Features:

- AC and DC test points provided directly on the power supply
- 60 and 90 volt AC powering capability
- Selectable AC under voltage lockout
- 30 volt lockout is for 60 volt systems (shipped in 30 volt lockout)
- 40 and 50 volt lockout are for 90 volt systems (can be changed in the field)
- Operating temp from -40° to 140°F (-40° to 60°C)
- +24 volts 2.5 Amp DC high-efficiency power supply
- Installs into any OEM 1 or 1.2 GHz housing and amplifier
- Installs into any BBI housing and amplifier with lid cover power supply option

| OEM P/N                  | BBI P/N     | Description  |
|--------------------------|-------------|--|
| N/A (EOL)                | 219PS214222 | 2.5 Amp Power Supply with Umbilical Cord/ Ladder Tray (Kit)        |
| 734771 or GM-PS-SA (EOL) | 219PS000    | 2.5 Amp Power Supply Only  |
| N/A (EOL)                | 214222000   | Umbilical Cord/Ladder Tray Only - for BBI or OEM system amplifiers |